

# Filtration



## Galvanized Filtertanks TOP

### Execution :

- Steel pressure vessels for filtration of water and non-corrosive liquids
- Carbon steel according EN 10025 or EN 10028
- Standard execution as well as made-to-measure
- Standard design pressure 7 bar
- Standard temperature -10°C / +50°C
- Accessible due to handholes
  - easy and fast mounting of internals, filling of filtermedia and service
- **TOP** Connection : 4'' - 8UN
- Pressure calculation code : AD-2000
- Conform PED 2014-68-EU-art.4§3, not for pneumatic applications
- Standard control : hydrostatic tested + manufacturers certification
- Finishing : hot dip- galvanized according EN 1461



### Internals :

- Filterstars 0.2 or 0.5 mm
- 6 arms 2'' or 8 arms 3''
- mat. PP – max. 60°C

Type	Volume	ø Dia	Cilindr. Height	Total Height	approx. weight	Top inlet	Drain	Inspection (n° flange)
F-38-T	200 L	380	1500	1890	+55kg	4''-8UN	1''	100x150 ( 3 )
F-50-T	320 L	500	1500	1850	+65 kg	4''-8UN	1''	100x150 ( 2 )
F-65-T	520 L	650	1400	1830	+95kg	4''-8UN	1''	100x150 ( 2 )
F-70-T	660 L	700	1500	1905	+110 kg	4''-8UN	1''	100x150 ( 0 )
F-80-T	975 L	800	1700	2200	+160kg	4''-8UN	1''	100x150 ( 0 )